

17680

High Pressure, Steel Wire Reinforced Air Hose. Also suitable for High Pressure Water & Slurries.

ID	OD	WP		WEIGHT
		PSI	BAR	KG/MT
3/4" (19mm)	31.4	600	40	0.82
1" (25mm)	37.8	600	40	1.07
1 1/4" (32mm)	48.0	600	40	1.79
1 1/2" (38mm)	55.6	600	40	2.10
2" (51mm)	66.8	600	40	2.35

Colour:
Yellow Cover/Black Lining

Cover:
EPDM Rubber. Weather & Abrasion resistant.

Lining :
EPDM Rubber, Oil Mist Resistant

Reinforcement:
2 plies High Tensile Steel Wire

Specification:
Fully complies to BS5118/3

Standard Coils:
20-40mtrs



18980

A medium pressure mandrel built multipurpose hose suitable for Air, Water and Oils.



Colour:
Black cover/lining

Cover:
CR/NBR rubber, resistant to weather, abrasion, oil & ozone.

Lining :
Black NBR, suitable for oil, greases & various solvents and some petroleum products

Reinforcement:
High strength textile plies & anti static wire.

Standard Coils:
40mtr coils

ID	OD	WP		WEIGHT
		PSI	BAR	KG/MT
1/2" (13mm)	23	300	20	0.50
3/4" (19mm)	32	300	20	0.70
1" (25mm)	38	300	20	0.80
1 1/4" (32mm)	46	300	20	1.10
1 1/2" (38mm)	52	300	20	1.40

90280

Hot Air Suction & Delivery Hose. Suitable for conveying Hot Air from compressors to tanks during the transfer of dry bulk material.

ID	OD	WP		WEIGHT
		PSI	BAR	KG/MT
1 1/2" (38mm)	48	150	10	1.07
2" (51mm)	61	150	10	1.39
2 3/8" (60mm)	72	150	10	1.88
2 1/2" (63mm)	75	150	10	1.96
3" (76mm)	88	150	10	2.64
3 1/2" (90mm)	104	150	10	3.15
4" (102mm)	116	150	10	3.52

Colour:
Blue cover/White lining

Cover:
EPDM

Lining :
EPDM, Heat resistant

Reinforcement:
High tensile cords with Embedded steel wire helix

Remarks:
-40°C to +165°C

