



LIGHTWEIGHT PETROLEUM

This hose is suitable for use with petroleum products, lubricating oils etc. Operating temperature -20°C to $+60^{\circ}\text{C}$. Widely used on Road tankers due to the aluminium internal wire, so reducing the overall weight of the hose. Sizes 2" to 4" bore.

Working pressure 7bar.

Fittings are available in Alloy, Gunmetal, Steel and Stainless Steel.

Swaged on end fittings ensure a permanent connection.

Standard Colour: Orange.

STANDARD PETROLEUM

This hose is suitable for use with petroleum products, lubricating oils etc. Operating temperature -20°C to $+60^{\circ}\text{C}$. Constructed with a galvanized internal and external wire increases the working pressure of this hose to 10bar. Sizes 2" to 4" bore.

Fittings are available in Alloy, Gunmetal, Steel and Stainless Steel.

Swaged on end fittings ensure a permanent connection.

Standard Colour: Black.

Max Length: 18.3mtrs



POLYPROPYLENE HOSE

General purpose chemical hose suitable for a wide range of chemicals. Operating temperature -30°C to $+60^{\circ}\text{C}$. Polypropylene lined hose with a polypropylene coated inner steel wire, but can also be made using a stainless steel inner wire. Sizes 1" to 4" bore.

Working pressure 14bar.

Fittings are available in Alloy, Gunmetal, Steel and Stainless Steel.

Swaged on end fittings ensure a permanent connection.

Standard Colour: Grey.

Max Length: 18.3mtrs

PTFE LINED HOSE

A PTFE lined composite hose for use with corrosive chemicals not suitable for use with the polypropylene lined version. Available in several grades depending on temperature and product being used. Temperature -30°C to $+160^{\circ}\text{C}$. (Dependant on grade of hose)

Supplied with Galvanized/Stainless Steel inner and external wire configurations

Sizes 1" to 4" bore.

Working pressures up to 14bar.

Fittings are available in Alloy, Gunmetal, Steel and Stainless Steel.

Swaged on end fittings ensure a permanent connection.

