

# 2680

# 90180

Suction of Air, Fumes, Gas, Powders and Sand Dust.

A high quality, very flexible ducting made from a thermoplastic coated polyester fabric encapsulating a semi-spring steel helix.



ID	WEIGHT	BEND RADIUS	VACUUM
mm	Grms/mtr	mm	M H <sub>2</sub> O
19	120	25	4
25	160	30	4
32	240	40	3.5
38	310	45	3
45	470	55	3
50	500	60	3
63	620	70	3
76	780	100	2.5
90	1050	140	2.5
100	1250	155	2.5
110	1400	170	2.5
125	1600	190	2.5
150	2000	200	2
160	2200	200	1.5
180	2500	220	1.5
200	2700	240	1.5
250	3680	280	1
300	4080	330	1

ID	WEIGHT	BEND RADIUS	VACUUM
mm	Grms/mtr	mm	M H <sub>2</sub> O
51	25	100	2300
57	25	100	2200
63	30	100	2000
70	30	100	1900
76	35	100	1750
82	35	95	1750
89	40	85	1750
102	40	85	1750
115	50	80	1650
127	55	75	1650
140	60	75	1500
152	65	70	1400
160	65	65	1380
178	75	60	1300
203	85	50	1250
229	95	45	1050
254	105	45	950
305	125	40	800

**Colour:**

Grey

**Applications:**

Plasticised PVC Ducting with a spiral reinforcement of Anti-shock rigid PVC.

Smooth bore and corrugated cover

**Temperature:**

-10° to +50°c

**Colour:**

Black

**Applications:**

Fume, dust, air and oil mist extraction.

**Temperature:**

-40° to +140°c